

SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

HYBRID ELECTRIC VEHICLE AUXILIARY OIL PUMP

Background of Invention

[0001] The present invention relates to an automatic transmission in a hybrid electric vehicle and more particularly to an automatic transmission in a hybrid electric vehicle where the engine shuts down when the vehicle stops.

[0002] Hybrid electric vehicles are vehicles that have a hybrid powertrain, typically including an electric drive system that is packaged in parallel with a conventional internal combustion engine. For hybrid electric vehicles with an internal combustion engine and an automatic transmission, it is preferable if the engine shuts down while the vehicle is stopped. By stopping the engine, the fuel economy of the vehicle is improved. However, the main transmission oil pump, which is typically driven by the rotation of the transmission input shaft, will stop pumping oil when the engine stops. But there is still a need for enough oil pressure to keep the clutches that are active in first gear (forward and low–reverse) stroked (i.e. engaged), so that the vehicle can immediately provide torque to the drive wheels when the vehicle operator demands a vehicle launch. If the oil pressure is not present, then the vehicle will not begin moving until the oil pressure can again build up to stroke the needed clutches. This would create an unacceptable delay for the vehicle operator.

[0003] Thus, it is desirable to have a hybrid electric vehicle with an automatic transmission, where the engine can shut down during a vehicle stop, but that also allows for immediate torque output when the vehicle operator demands a vehicle launch.

Summary of Invention

[0006] An embodiment of the present invention allows for the addition of an electronically controllable transmission oil auxiliary pump, and a shut-down shuttle valve, so that there is enough oil pressure at the forward and the low-reverse clutches to allow for a quick vehicle launch, even when the vehicle engine is shut down while the vehicle is stopped.

[0008] Another advantage of the present invention is that the hybrid electric vehicle can begin transmitting torque to the drive wheels immediately upon driver demand for the torque, even when the engine is shut down during a vehicle stop.

[0009] A further advantage of the present invention is that the hydraulic pressure needed to obtain an immediate vehicle launch after the vehicle is stopped is produced with minimal additional hardware versus a conventional automatic transmission, and with minimal parasitic losses from generating the needed hydraulic pressure.

Brief Description of Drawings

[0010] Fig. 1 is a schematic diagram of a portion of a hybrid electric vehicle powertrain in accordance with the present invention.

[0011] Fig. 2 is a schematic diagram of a valve body and clutches for an automatic transmission in accordance with the present invention.

[0012] Fig. 3 is a schematic diagram of electronic and hydraulic circuits for an auxiliary pump in accordance with the present invention.

[0013] Fig. 4 is a flow chart illustrating a process for operating an auxiliary pump in a hybrid vehicle, in accordance with the present invention.

Detailed Description

[0014] Fig. 1 illustrates a hybrid electric vehicle 10 that includes an internal combustion engine 12, a electric traction motor 14 and an automatic transmission 16. The engine 12 includes a crankshaft 18 that connects, via a clutch 20, to a main shaft 22 of the traction motor 14. The traction motor main shaft 22 also connects to an input shaft 24 of the transmission 16, which connects, via the transmission gears (not shown), to a transmission output shaft 25. A main transmission oil pump 26 mounts to and is driven by the input shaft 24. The transmission 16 also includes an oil pan 28 and a valve body 30. Electrically connected to components within the valve body 30 is a transmission control module 32. The electrical connections are illustrated herein by dashed lines. The transmission control module 32 controls the shifting of the transmission 16, via the valve body 30.

[0015] Fig. 2 shows a schematic diagram of the valve body 30 and hydraulic connections to clutches and bands in the transmission. The valve body 30 includes a low-reverse solenoid 36, a two/four solenoid 38, a direct solenoid 40, a forward-reverse solenoid 42, and an EPC solenoid 44. The actuation of these solenoids is electronically

[0017] The transmission also includes an electrically driven, auxiliary pump 78, a pump outlet pressure transducer 80, and a forward clutch pressure transducer 82, which are hydraulically linked to a shut down shuttle valve 84 in the valve body 30. The shut down shuttle valve 84 is interposed in the hydraulic circuit 67 between the low-reverse shuttle valve 52 and the low-reverse clutch 68, and between the forward-reverse shuttle valve 58 and the forward clutch 76. The line pressure produced by the main transmission oil pump connects to one side of the shut down shuttle 84, while the auxiliary pump pressure is connected to the other side of the shut down shuttle 84. When the line pressure is higher, the shuttle 84 moves so that the low-reverse clutch 68 is in hydraulic communication with the low reverse shuttle valve 52, and the forward clutch 76 is in hydraulic communication with the forward-reverse shuttle valve 58. When the auxiliary pump pressure is higher, the shuttle moves so that the low-reverse clutch 68 and the forward clutch 76 are selectively in hydraulic communication with the auxiliary pump 78.

[0018] Fig. 3 better isolates the hydraulic circuit 67 and the electronic circuit 89 for the auxiliary pump 78 from the rest of the hydraulic circuit shown in Fig. 2. The main hydraulic pressure regulator valve 46 supplies a hydraulic line pressure to the low-reverse solenoid 36 (and ultimately to an inlet 85 to the shut down shuttle 84), to another inlet 86 of the shut down shuttle 84, and to one end 88 of the shut down shuttle 84 for actuating the shuttle 84. The inlet of the auxiliary pump 78 is connected to a source 90 of hydraulic oil. The auxiliary pump outlet is connected to a pair of inlets 94, 95 of the shut down shuttle 84, and to the other end 92 of the shut down shuttle 84 for actuating the shuttle 84.

[0019] The position of the shut down shuttle is determined by the higher of the line pressure and the auxiliary pump pressure. The inlet 85 connects to an outlet 96 and the inlet 86 connects to an outlet 97 when the line pressure is higher than the auxiliary pump pressure, and the inlet 95 connects to the outlet 96 and the inlet 94 connects to the outlet 97 when the auxiliary pump pressure is higher. So effectively, when the pressure from the auxiliary pump 78 is higher than the line pressure, the normal hydraulic circuits to both the forward clutch 76 and the low-reverse clutch 68 are interposed, and the shut down shuttle 84 provides a new source of hydraulic pressure for actuating the low-reverse clutch 68 and the forward clutch 76.

[0020] The auxiliary pump 78 is electrically driven by a steady state relay 98 based on pulse width modulated signals from a pump controller 99, which is in communication with the pressure transducers 80, 82 and the transmission control module 32. This electronic circuitry 89 allows for a constant pump pressure from the auxiliary pump 78. While the pump controller 99 and transmission control module 32 are shown separately, the pump controller 99 can be integrated into the transmission control module 32, if so desired.

[0021] Fig. 4 shows a flow chart for the process of controlling the auxiliary pump 78, hydraulic circuit 67, and electrical circuit 89, of Figs. 1-3. When the hybrid electric vehicle 10 comes to a stop, the engine 12 shuts down, block 102. Next, it is determined if the transmission selector lever is in drive or low, block 104. If not, then the auxiliary pump strategy is not started, block 106. If it is in drive or low, then the auxiliary pump strategy is initiated, block 108. It is then determined if the speed of

the transmission input shaft 24 is less than a predetermined threshold speed, block 110. If it is not, then the strategy begins again. If the speed is less than the threshold, then the auxiliary pump 78 will be activated in open loop mode for a predetermined time interval T, block 112. This open loop pump operation is used to prime the auxiliary pump 78. Then, when the time interval T has expired, the auxiliary pump 78 is operated at a rate that will produce a pressure that is about equal to the line pressure for normal transmission operation, block 114. During this process, as the pressure from the auxiliary pump 78 begins to exceed the line pressure, the pressure difference will automatically cause the shut down shuttle 84 to shift. This shift will change the hydraulic circuit 67 so that the low–reverse clutch 68 and the forward clutch 76 will be actuated by the pressure created from the auxiliary pump 78.

[0022] The auxiliary pump continues to run in open loop mode until a predetermined pressure threshold is exceeded, block 116. The pressure produced by the auxiliary pump is determined by inputs from the pump outlet pressure transducer, and the forward clutch pressure transducer. Once the pressure threshold is exceeded, the auxiliary pump is operated with closed loop control, block 118, in order to maintain the constant desired pressure. The constant desired pressure from the auxiliary pump 78 is preferably controlled to a level that is below that of the normal hydraulic pressure resulting from the operation of the main pump. This constant pressure is maintained so that the low–reverse clutch and the forward clutch remain engaged, ready for an immediate vehicle launch. By employing the pressure transducers 80, 82 to allow for closed loop control of the hydraulic pressure from the auxiliary pump 78, the hydraulic pressure supplied for these clutches can be maintained at the lowest level required to maintain clutch engagement. Thus, the power consumption of the auxiliary pump 78 can be minimized.

[0023] Once the vehicle launches, then the transmission input shaft will begin driving the main transmission oil pump, which will then begin building line pressure again. When the transmission input shaft speed exceeds a predetermined threshold speed, block 120, the auxiliary pump will be turned off, block 122, which will end the auxiliary pump strategy, block 124, until the vehicle again stops. Of course, as the transmission input shaft gains speed during vehicle launch, the main transmission oil pump will increase the line pressure. Thus, in turn, the shut down shuttle will be

shifted to disconnect the auxiliary pump from the hydraulic circuit and connect the low-reverse clutch and the forward clutch to the normal operating hydraulic circuit for the transmission.

[0024] While certain embodiments of the present invention have been described in detail, those familiar with the art to which this invention relates will recognize various alternative designs and embodiments for practicing the invention as defined by the following claims.